


KODAK Solar Battery Storage NL10.0




Floor Mounted Battery Storage

Features

- Easy for installation and maintenance with software BMS monitoring
- Can be easily stand on the floor
- Support high current charging / discharging
- Support RS485,RS232 and CAN communications
- Performance rate of 1C
- Compatible with most leading brands of inverters
- 6000+ cycle life (see technical data below)
- LCD display
- Compact and slimline design
- Support up to 15 packs in parallel
- Warranty 10 years
- Compatible with most inverters and chargers

Models:

KODAK Solar Battery Storage NL10.0



Technical Parameters

Model	NL10.0
Nominal Voltage	51.2V
Nominal Capacity	200Ah
Nominal Battery Energy	10.24KWh
Charging cut-off voltage	58.4V
Discharging cut-off voltage	44.8V
Max.Continuous Charging Current	200A(Recommend 100A)
Max.continuous Discharge Current	200A
Max C Rating	1C
Parallel Capability	Up to 15 units
Communication	RS485/RS232/CAN
Cycle Life	> 6000 cycles @80%DOD&1C
Warranty	10 years
Certification& Safety standard	CE/UN38.3/MSDS
Operating Temperature	Charging:0 to +50 °C, Discharging:-10 to +50 °C
Storage Temperature	-10 °C to +55 °C
Protection	Over-charge/Over-discharge/Over-current/Over-temperature/Short Circuit
Net Weight	97KGS
Dimension	820*590*161mm



For further information visit www.bluemountainpv.com

©2024 Blue Mountain Energy LTD, The Kodak trademark, logo and trade dress are used under license from Kodak

Blue Mountain Energy Ltd. Crown House, 27 Old Gloucester Street, London WC 1N 3AX

Made in China